

2001 Rexford Road Charlotte, North Carolina 28211

For Emergency Product Information Call: Director Quality Services (704) 365-7543

Material Safety Data Sheet Gold Bond BRAND Miscellaneous Gypsum Products MSDS No: GB-1201 January 26, 2004 Dated:

1. **Product Identification**

Product Name: Product Number(s): Gypsum Accelerator Agricultural Gypsum Land Plaster PL9050

Cement Rock

Use:

GB 8582 PL6750

Accelerate set of gypsum plaster, Stabilize soil, Accelerate set of cement

PL0019

PL3390

Generic Descriptions:

Gypsum rock

Article composite

Calcium Sulfate Dihydrate

2. Composition/Information on Hazardous Ingredients

		Exposure Limits	
Contains: Chemical Identity	CAS-NO	OSHA PEL (mg/m3)	ACGIH TLV (mg/m3)
Gypsum	10101-41-4	5	10 ^A
Quartz ^B	14808-60-7	С	0.1

Contains no asbestos. HMIS Hazard Class No. 1, 0, 0.

Total dust. All others are respirable dust.

Present as a naturally occurring component of minerals. See Sec. 3 HEALTH HAZARDS IDENTIFICATION

Ç Respirable dust. Use the formula 10 mg/m³

Appearance and Odor: A white solid/powder with no odor.

3. Health Hazards Identification

- Route(s) of Entry: Inhalation and Dermal
- Potential Health Effects: Skin and eye irritant

Quartz (crystalline silica) - The International Agency for Research on Cancer (IARC) classifies crystalline silica inhaled in the form of quartz or cristobalite from occupational sources as carcinogenic to humans, Group 1. The National Toxicology Program (NTP) classifies respirable crystalline silica as a substance, which may be reasonably anticipated to be a carcinogen. OSHA does not regulate crystalline silica as a human carcinogen.

It is recommended that a NIOSH approved respirator, for toxic dusts, be worn whenever working with this product results in airborne dust exposure exceeding the prescribed limits.

Skin Contact: Continued and prolonged contact may result in dry skin.

Eye Contact: Direct contact may cause mechanical irritation.

Inhalation: Target Organ: respiratory system

Dated: January 26, 2004

Signs and Symptoms of Exposure to Airborne Dust: Continued and prolonged exposure to airborne dust concentrations in excess of the PEL/TLV may result in cough, dyspnea, wheezing, and impaired pulmonary function.

Medical Conditions Generally Aggravated by Exposure: Overexposure would generally aggravate respiratory system dysfunctions.

4. First Aid Measures

First Ald Procedures:

- · Eye: Immediately flush eyes with water for 15 minutes and get medical attention.
- Skin: Flush and wash skin with soap and water. Get medical attention if irritation persists.
- **Breathing:** Move the exposed person to fresh air at once, if not breathing initiate pulmonary resuscitation. Get medical attention.

5. Fire Hazards

- Not Combustible
- NFPA Hazard Class No: 1/0/0
- · Extinguishing Media: Dry chemical, foam, water, fog or spray.

Special Fire Fighting Procedures: Wear full protective equipment and an approved pressure demand self-contained breathing apparatus (SCBA).

6. Precautions For Safe Handling

- Steps to be taken in Case Material is Released or Spilled: Shovel or scoop up back into container for use if possible or disposal.
- Waste Disposal Method: Not a hazardous waste. Dispose of in accordance with applicable federal, state, and local regulations.
- · Precautions to be taken in Handling and Storing: Keep dry to preserve usefulness.

7. Stability and Reactivity

Stability and Reactivity: Gold Bond[®] BRAND Gypsum is stable and hazardous polymerization will
not occur. When heated to decomposition, oxides of sulfur will be released.

8. Exposure Controls/Personal Protection

- Work/Hygiene Practices: Avoid creating dust.
- Ventilation: Provide ventilation to maintain a dust level below the PEL/TLV.
- Respiratory Protection: A NIOSH approved respirator for toxic dusts is recommended if the PEL/TLV is exceeded.
- Eye Protection: Safety glasses or goggles.

9. <u>Transport Information</u>

DOT: Not regulated

10. Regulatory Information

SARA Title III Section 313 Ingredients

None at or above the de minimus level.

11. Other Information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind expressed or implied is made with respect to the information contained herein. This material safety data sheet was prepared to comply with the OSHA Hazard Communication Standard (29 CFR 1910.1200) and with the Workplace Hazardous Materials Information System (WHMIS). This supersedes any previous information.

Dated: January 26, 2004

Disclaimer of Liability:

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of the material. Information contained herein is believed to be true and accurate, but all statements or suggestions are made without any warranty, express or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained for the use thereof.